

Pos.	Stück	Bezeichnung	Einzelpreis DM	Gesamtpreis DM
0004	1	ACCESSIBLE FOR CLEANING, COMBINED W. AIR DUCT PANEL, WITH LOWER, CENTER AND UPPER EXTRACTION. ILLUMINATION W. FLUORESCENT LAMP 220 V, 36 WATT AND HEAVY-DUTY REFLECTOR. WORK TOP RED BROWN TILED. W. BASE CABINET EXTRACTION		
	1	NIPPLE FOR CONNEXION OF VENTILATION LINE AT CABINET 200 MM DIAMETER		
	1	CONTROLLING AND SIGNAL DEVICE OF THE VENTILATION FUNCTION FOR HOODS ACC. DIN 12924 PART 1 COMPLETE WITH ALARM LAMP AND OSCILLATOR MOUNTED AND WIRED		
	1	OFF-SWITCH, 1 POLE 220 V, A.C. MOUNTED AND WIRED		
	1	TRIPLE PUSH BUTTON I-O-II WITH CONTROL FOR AERATION MOUNTED AND WIRED		
	2	CONTACTOR WITH RELAY METAL-CLADDED.		
	2	SAFETY SOCKET 220 V, A.C. WITH LIFT-UP LID IP 44 MOUNTED IN THE HOOD		
	1	WIRING 220 V FOR SOCKETS WIRING 3 X 1,5 QMM		
	2	OFF-SWITCH, 1 POLE 220 V, A.C. MOUNTED AND WIRED		
	2	SAFETY SOCKET 220 V, A.C. WITH LIFT-UP LID IP 44 MOUNTED		
	1	WIRING 220 V FOR SOCKETS WIRING 3 X 1,5 QMM		
	1	GENERAL MOUNTING COSTS		
	1	ACID RESISTENT CENTRIF. FAN THREE-PHASE CURRENT, PRO- TECTION IP 44, IMPELLER OF PPH, CASE OF PVC-H WITH FORMED SUCTION AND EXHAUST NOZZLE. PVC CONNEXION PIECES. SUPPORT FRAME PLASTIC COATED WITH FIXING CLIPS. SUCTION AND EXHAUST DIA 200 SPLINTER PROTECTION MOTOR SPEED 1500 R.P.M. CAPACITY 500-1400 CBM/H STRUCTURE - FROM THE DRIVING SIDE; CLOCKWISE		